

PANEL

Screen Size	49"
Panel Technology	IPS
Back Light Type	Direct
Aspect Ratio	16 : 9
Native Resolution	1,920 x 1,080 (FHD)
Refresh Rate	60Hz
Brightness	500nit (Typ.)
Contrast Ratio	1,000:1
Dynamic CR	500,000 : 1
Color gamut	NTSC 72%
Viewing Angle(H x V)	178x178
Color Depth	10bit, 1.07Billion colors
Response Time	8 ms (G to G)
Surface Treatment(Haze)	3%
Life time	60,000Hrs (Typ.) / 50,000Hrs (Min.)
Operation Hours (Hours/Day)	24/7
Portrait / Landscape	Yes / Yes

CONNECTIVITY

Input	HDMI (2, HDCP 1.4), DP (1, HDCP 1.3),DVI-D (1, HDCP 1.4)
-------	--

Audio In, RS232C IN, RJ45(LAN), IR IN, USB2.0 Type A (1)

OutputDP Out, Audio Out, RS232C OUT

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	T/R/L/B : 2.25/1.25/2.25/1.25mm
Weight(Head)	16.9Kg
Packed Weight	29.3kg
Monitor Dimension(W x H x D)	1077.6 x 607.8 x 89.7mm
Carton Dimensions(W x H x D) (Box outer size)	1214 x 778 x 263mm
Handle	Yes
VESA™ Standard Mount Interface	600 x 400

KEY FEATURE

HW - Sensor - Temperature Sensor	Yes
SW - Embedded CMS - Local Contents Scheduling	Yes
SW - USB Plug & Play	Yes
SW - Fail over	Yes
SW - Background Image - Booting Logo Image	Yes
SW - Background Image - No Signal Image	Yes
SW - Sync Mode - RS-232C Sync	Yes

SW - Rotation - Screen Rotation	Yes
SW - Tile Mode Setting	Yes (Max. 15x15)
SW - Setting Data Cloning	Yes
SW - SNMP	Yes
SW - ISM Method	Yes
SW - Auto Set ID	Yes
SW - 3rd Party Compatibility - Crestron Inside	Yes
SW - Power - Smart Energy Saving	Yes
SW - Power - PM mode	Yes
SW - Power - Wake on LAN	Yes
SW - HDMI-CEC	Yes
SW - SI Server Setting	Yes
SW - W/B Setting by Grey scale	Yes
SW - Scan Inversion	Yes

ENVIRONMENT CONDITIONS

Operation Temperature	0 °C to 40 °C
Operation Humidity	10 % to 80 %

POWER

Power Supply	AC 100-240V~, 50/60Hz
Power Type	Built-In Power

POWER CONSUMPTION

Typ.	100W
Max.	120W
BTU (British Thermal Unit)	341 BTU/Hr(Typ.), 409 BTU/Hr(Max)
Smart Enegy Saving	60W
DPM	0.5W
Power off	0.5W

CERTIFICATION

Safety	CB / NRTL
EMC	FCC Class "A" / CE / KC
ErP / Energy Star	Yes / Energy Star 8.0(US Only)

SOFTWARE COMPATIBILITY

SuperSign CMS	Yes
SuperSign Control / Control+	Yes / Yes
SuperSign WB	Yes
SuperSign Media Editor	Yes
Connected Care	Yes

LANGUAGE

OSD	English, French, German, Spanish, Italian, Korean , Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Japanese, Russian, Portugues(Europe), Dutch, Czech, Greek, Arabic
-----	---

ACCESSORY

Basic

Remote Controller(include battery 2ea), Power Cord, RS232C cable, DP cable, IR Receiver, Guide Bracket, Screws, Manual

Optional

Wall Mount (Landscape : WM-L640V, Portrait : WM-P640V)
